



Coversafe Automatic Pool Covers - Construction Dimensions

Pools up to 50' Long				
	0-16' Wide/up to 32' Long - CS300HD	0' - 22' Wide Eclipse/CS3000	22' - 28' Wide Eclipse/CS3000	28'-34' Wide Eclipse/CS3000
Box Width	14"	14"	16"	17"
Box Depth	16"	16"	16"	18"
Motor Side Offset	15"	30"	30"	30"
Non Motor Side Offset	9"	12"	12"	12"
Roll-up Tube Size	4"	6"	6"	8"
Leading Edge Diameter/Thickness	1 1/2"	2 1/2"	4"	5"
Bond Beam and Spa Clearance (Normal Stone Lid)	2"	2"	2"	2"
Bond Beam and Spa Clearance (Hidden Leading Edge)	3"	4"	6" (up to 25' Wide)	N/A
Clearance of water side of common wall (Slanted wall instead of notched)	5"	6"	N/A	N/A
Clearance of box side of common wall (Slanted wall instead of notched)	2"	2"	N/A	N/A
Distance from bottom of coping to water level if Hidden Leading Edge	3"+	4"+	6"+	N/A

Pools Longer than 55' and shorter than 75'				
	0-16' Wide/up to 32' Long - CS300HD	0' - 22' Wide Eclipse/CS3000	22' - 28' Wide Eclipse/CS3000	28'-34' Wide Eclipse/CS3000
Pool Width				
Box Width	14"	16"	17"	18"
Box Depth	16"	16"	18"	20"
Motor Side Offset	30"	30"	30"	30"
Non Motor Side Offset	12"	12"	12"	12"
Roll-up Tube Size	6"	6"	6"	8"
Leading Edge Diameter/Thickness	1 1/2"	2 1/2"	4"	5"
Bond Beam and Spa Clearance (Normal Stone Lid)	2"	2"	2"	2"
Bond Beam and Spa Clearance (Hidden Leading Edge)	3"	4"	6" (up to 25' Wide)	N/A
Clearance of water side of common wall (Slanted wall instead of notched)	5"	6"	N/A	N/A
Clearance of box side of common wall (Slanted wall instead of notched)	2"	2"	N/A	N/A
Distance from bottom of coping to water level if Hidden Leading Edge	3"+	4"+	6"+	N/A

Coversafe, Inc.
Phone: 860-283-6699