# CoverSafe, Inc. CoverSafe, Inc.CoverSafe.comCoverPools Automatic PoolPh: 866-746-8444

CoverSafe.com **Cover Information Sheet** Fax: 866-799-4911

#### **BUILDER INFORMATION**

Name:		Contact:			
Address:					
City:	State:		Zip:		
Office Phone:	Cell Phone:		Fax:		
Email:					
JOB SITE INFORMATION					
Name:					
Address:					
City:	State:		Zip:		
Home Phone:		Cell Phone:			
Email: (Required for Warranty Registration)					
Special directions to job site:					

# **POOL INFORMATION**

Track Dimensions:	Cover Model:
Track Space:	◯ T4 Spa
ftinTrack Length:ftin	Mechanism Type: Undertrack Toptrack Deck Motor Type:
Drop to Water: in Track Space	○ Electric ○ Hydraulic Motor Side:
Pool Type:          Gunite/ Shotcrete       Vinyl Liner         Pool Shape:          Rectangle       Free Form	(Viewed from behind the cover box looking across the pool)     Cover Box       Right     L       Undecided     Motor Side:

# **OPTIONS**

Channel 1	Гуре:
-----------	-------

#### ○ None

O Bullnose / Vinyl Liner Coping

- Fiberglass
- ⊖ Gunite
- Vinyl Liner with Retainer
- Coping Forms

## Track Options:

- $\bigcirc$  Dual Race Track  $\bigcirc$  Underside Track
- $\bigcirc$  Snap Toptrack  $\bigcirc$  Vanishing Edge

# Vanishing Edge:

○ No ○ Left

○ Left
 ○ Right
 ○ VE 45
 ○ VE 90

VE Track Height Difference:

# **UPB Box:**

○ None

○ None

# Aluminum Lid Types:

- None
- Flat Bezel Lid
- Std Aluminum Lid
- O Tilted Bezel Lid
- Flush Lid

#### Corners: (Vinyl Liner Pools Only)

None6" Radius

○ 90 Degree
 ○ 2 Ft Radius

○ Include UPB Box

○ 3" Chop

## Bench Installed by Coversafe: (Deckmount Systems Only)

- None Pressure Treated
- Cedar Everlast bench
- O Everlast bench ends

# **Control Type:**

- Toggle Switch w/ Clutch
- Toggle Switch w/ AutoShutoff Board
- O Coverlink Touchpad w/ Clutch
- Coverlink Touchpad w/ AutoShutoff Board

## Water Feature Interrupt Option?

◯ Yes ◯ No

Pool Controller Brand: (To determine water feature interrupt)

- None Hayward
- Jandy Pentair

# Input Device:

- None
- O Rotational Counter
- Limit Switch and Magnet

# Installation by Coversafe?

## ○ No

- Phase 1 Phase 2

# Leading Edge:

- O Rope / Bead (Standard)

⊖ Yes

○ Wrap (2 1/2" square only)

# Walk on Stone Lid Brackets:

- None
- 12" Lid Bracket
- 14" Lid Bracket
- 14.5" Lid Bracket (Extends 1") Adjustable from 12" 14.5"
- 17.5" Lid Bracket (Extends 1") Adjustable from 15" 17.5"

⊖ Sewn

- 18" Lid Bracket
- O 20.5" Lid Bracket Adjustable from 15" 20.5"
- 23.5" Lid Bracket Adjustable from 21" 23.5"
- O Hidden Leading Edge Bracket 21"

### Webbing Type:

○ Heat Sealed

### Fabric Type:

- Quad-Core™ Laminated Fabric
- Pro-Coat<sup>™</sup> Coated Fabric

#### Fabric Color: (Based on fabric type choice) Quad-Core™ Laminated Fabric:



Both